
PVC, PU & FABRIC BELTING

Blue 2-Ply PU Conveyor Belt



Fabric-reinforced conveyor belting with a specified surface and underside. Include belt travel, cleaning conditions and splice requirements; request food-contact documentation for the exact supplied belt.

Unit for enquiry: metre | Reference: CB-2P-PU-B

Product range reference. Colour and supplied configuration are confirmed with your quotation.

PRODUCT DETAILS

Reference	CB-2P-PU-B
Belt thickness	1.6 mm
Top cover	0.3 mm
Belt mass	1.65 kg/m2
Minimum pulley at ambient	25 mm
Published temperature range	Product: -40 to +90 deg C; ambient: -25 to +60 deg C
Published stock width	2000 mm; requested cut width to confirmation
Minimum backflex at ambient	50 mm

TYPES / CONFIGURATIONS

CB-2P-PU-B

Choose your enquiry specification below. Stock, final dimensions and operating suitability are confirmed in the quotation. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Blue 2-Ply PU Conveyor Belt

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Supply format	Endless finished belt, Open length, Replacement belt to sample
Finished belt length / circumference (mm)	Complete endless circumference, or open cut length
Finished belt width (mm)	Width across the belt
Fabric plies	2 ply
Joint / splice	Finger splice, Step / overlap splice, Mechanical fastener, Open ends - no joint, Match existing joint
Belt construction	PU carrying surface
Total thickness (mm)	Measured total thickness, including covers
Surface / underside / colour	Smooth, rough top, coated, fabric back, colour
Flights, guides and edge details	Height, pitch, section, position and sidewalls
Smallest pulley / nosebar diameter (mm)	Include reverse bending and knife-edge details
Application and operating conditions	Product, duty, temperature and environment
Manufacturer / complete reference	Include every prefix, suffix and marking

INCLUDE WITH YOUR ENQUIRY

State finished endless circumference or open cut length, width, total thickness, material/ply specification, surface and underside, splice type, smallest pulley, flights/guides and operating conditions. Quantity is ordered separately from belt dimensions. Request food-contact documentation for the exact product when needed.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.