CONVEYORS & BELTING

Conveyor Chain Idler Wheels



Solid and split idler wheels for the non-driven end of a conveyor. Match the chain series, shaft and wheel diameter before ordering.

Unit for enquiry: each | Reference: D00001

Product range example; confirm the make and configuration quoted.

PRODUCT DETAILS

Reference chain series	812 / 815 / 820 / 828 / 881M / 881MO
Construction	Solid or split
Dimensions	Wheel diameter, bore and face width

TYPES / CONFIGURATIONS

Solid idler wheel | Split idler wheel

This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Conveyor Chain Idler Wheels

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Wheel outside diameter	Enter your dimensions / reference, or ask for help identifying the item.
Shaft / bore size	20 mm, 25 mm, 30 mm, 35 mm, 40 mm, 45 mm, 50 mm
Wheel face width (mm)	Measured wheel width
Chain series	812, 815, 820, 828, 881M or 881MO

INCLUDE WITH YOUR ENQUIRY

Chain series, outside diameter, face width, bore size, shaft shape and number of wheels.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.