FESTO PNEUMATIC COMPONENTS

Festo ADN Compact Pneumatic Cylinders



Compact double-acting cylinders for short installation spaces on packaging and production machinery. Match bore, stroke, piston-rod thread and cushioning to the machine.

Unit for enquiry: each | Product range

Festo product-family image. Exact size, connections and configuration are confirmed with your quotation.

PRODUCT DETAILS

Action	Double-acting ADN
Family bore range	12 to 125 mm; configuration dependent
Cushioning	P elastic or PPS self-adjusting pneumatic, as ordered
Rod thread	Male or female variants
Example	ADN-32-25-A-P-A / 536272: 32 mm bore, 25 mm stroke, G1/8 ports

TYPES / CONFIGURATIONS

Cylinder only | Cylinder with mounting accessories | Cylinder with compatible sensors

ISO 21287 conformity depends on bore; the family includes compliant and based-on variants. Confirm the chosen model, load, speed, cushioning, washdown exposure and end-stop energy. Do not assume side-load capacity or direct food contact. Options describe an enquiry; not every combination is available. Confirm the complete selected reference and operating limits before ordering. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Festo ADN Compact Pneumatic Cylinders

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Cylinder bore (mm)	12 mm, 16 mm, 20 mm, 25 mm, 32 mm, 40 mm, 50 mm, 63 mm, 80 mm, 100 mm, 125 mm
Required stroke (mm)	Exact stroke and existing cylinder reference
Mounting and rod / guide dimensions	Mounting centres, rod thread, port size and available space
Load, speed and cushioning	Load and offset, orientation, speed and cushioning type
Sensors and accessories required	Complete switch reference, cable / connector and mounting kit
Medium, operating pressure and temperature	Normal / maximum pressure in bar, medium, temperature and air quality
Complete manufacturer reference / existing markings	Include every suffix if known; otherwise ask for identification help

INCLUDE WITH YOUR ENQUIRY

Send the complete reference, requested size and configuration, operating conditions, quantity, delivery location and required date. Add label / installation photographs and state whether an alternative may be proposed for approval.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.