FESTO PNEUMATIC COMPONENTS

Festo DSBC ISO Pneumatic Cylinders



ISO 15552 double-acting cylinders for industrial machine actuation. Choose cushioning and mounting to suit the stroke, speed and moving load.

Unit for enquiry: each | Product range

Festo product-family image. Exact size, connections and configuration are confirmed with your quotation.

PRODUCT DETAILS

Standard	ISO 15552
Action	Double-acting
Cushioning options	P elastic, PPS self-adjusting pneumatic, PPV adjustable pneumatic
Position feedback	Compatible proximity sensing arrangement required
Example	DSBC-32-100-PPSA-N3 / 1376471; verify complete suffix before replacement

TYPES / CONFIGURATIONS

Cylinder only | Cylinder with mounting accessories | Cylinder with compatible sensors

Check mounting, rod length and thread, port position, cushioning and temperature options when replacing an ISO cylinder. Locking or clamping variants need a separate application assessment; a standard cylinder does not provide a safety-rated holding function. Options describe an enquiry; not every combination is available. Confirm the complete selected reference and operating limits before ordering. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Festo DSBC ISO Pneumatic Cylinders

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Cylinder bore (mm)	32 mm, 40 mm, 50 mm, 63 mm, 80 mm, 100 mm, 125 mm
Required stroke (mm)	Exact stroke and existing cylinder reference
Mounting and rod / guide dimensions	Mounting centres, rod thread, port size and available space
Load, speed and cushioning	Load and offset, orientation, speed and cushioning type
Sensors and accessories required	Complete switch reference, cable / connector and mounting kit
Medium, operating pressure and temperature	Normal / maximum pressure in bar, medium, temperature and air quality
Complete manufacturer reference / existing markings	Include every suffix if known; otherwise ask for identification help

INCLUDE WITH YOUR ENQUIRY

Send the complete reference, requested size and configuration, operating conditions, quantity, delivery location and required date. Add label / installation photographs and state whether an alternative may be proposed for approval.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.