CONVEYOR ROLLERS & DRIVES

Gravity Conveyor Rollers



Free-running rollers for push conveyors, gravity lanes, packing tables and carton or tote transfer. Match the bearing arrangement and starting resistance to the weight of the goods, as well as the roller diameter and conveyor frame.

Unit for enquiry: each | Product range

Manufacturer range illustration. The supplied make, dimensions, drive head and finish are confirmed in your quotation.

PRODUCT DETAILS

Movement	Manual push or gravity; no powered drive head
Dimensions	Tube diameter, face length, shaft ends and installation width
Selection	Small/light products need suitable roller spacing and low starting resistance
Environment	Confirm bearing/seal and tube material for wet, cold or dusty duty

TYPES / CONFIGURATIONS

Straight gravity roller | Spring-loaded shaft | Threaded shaft ends | Stainless steel enquiry

These fields describe your enquiry. Final dimensions, loading, speed, environmental suitability and lead time must be confirmed for the selected roller. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Gravity Conveyor Rollers

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Tube outside diameter (mm)	Measure the roller tube, not the sprocket
Roller face length and between-frame length (mm)	State both dimensions separately, or ask for help identifying
Shaft diameter and end mounting	Thread size, spring-loaded shaft, flats or drawing reference
Tube material / finish	Zinc-plated steel, Stainless steel, PVC, Match existing roller
Load, conveyor speed and environment	Item weight, rollers supporting it, wet/dry duty and temperature
Existing roller code / drawing	Manufacturer code, RL / EL / AGL markings or photo reference
Shaft mounting	Spring-loaded, Female threaded, Hex / flats, Match existing roller

INCLUDE WITH YOUR ENQUIRY

Send roller diameter, face length, between-frame length, shaft ends, material, drive details, quantity and required date. A drawing or clear photographs help us match the replacement.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.