MOTORS, GEARBOXES & DRIVE COMPONENTS

Parallel-Shaft Helical Gearboxes



Offset parallel-shaft reduction drives for conveying and processing equipment where a slim installation is useful. Hollow- and solid-shaft configurations allow different machine connections.

Unit for enquiry: each | Product range

Product-family photograph. Exact model, dimensions and configuration are confirmed with your quotation.

PRODUCT DETAILS

Gear arrangement	Parallel-shaft helical
Mounting	Foot, flange or shaft mounted
Output	Solid or hollow shaft, according to model
Connections	Keyed, shrink-disc or spline variants subject to selection

TYPES / CONFIGURATIONS

Solid shaft | Keyed hollow bore | Shrink-disc hollow bore | Splined connection | Match existing

Specify shaft tolerances, reaction support and installation clearance for a hollow-shaft assembly. Reduced backlash is a separate configuration, not a standard family-wide claim. Choices record your requested specification; not every combination is available. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Parallel-Shaft Helical Gearboxes

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Required assembly	Gearbox only, Complete geared motor, Replacement matching existing unit
Ratio / required output speed	Nameplate ratio or required output rpm
Input speed and motor power	Motor kW and rated input rpm
Output torque and load duty	Continuous / peak Nm if known; load, hours and starts
Output shaft / bore dimensions	Diameter, length, keyway / spline and flange pattern (mm)
Mounting and operating position	Foot / flange / torque arm, orientation and shaft side
Application and environment	Driven equipment, hours / starts, ambient temperature, dust and cleaning conditions
Existing model / complete reference	Full reference and suffixes; include a clear nameplate photograph
Output connection	Solid shaft, Keyed hollow bore, Shrink-disc hollow bore, Splined connection, Match existing
Mounting style	Foot mounted, Flange mounted, Shaft mounted

INCLUDE WITH YOUR ENQUIRY

Send the complete reference and nameplate photo, installation dimensions, operating duty, quantity, delivery location and required date. State whether an alternative may be proposed for approval.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.