
PVC, PU & FABRIC BELTING

PTFE / Teflon Conveyor Belts



PTFE-coated glass-fibre belts and mesh belt enquiries for processing equipment. Specify mesh opening or solid fabric, total thickness, finished dimensions, joint and edge reinforcement, together with the actual temperature and product being conveyed.

Unit for enquiry: metre | Product range

Product range reference. Colour and supplied configuration are confirmed with your quotation.

PRODUCT DETAILS

Range	PTFE / Teflon Conveyor Belts
Dimensions	Width, length, thickness and joint to specification
Operating limits	Confirm the exact material and belt reference

TYPES / CONFIGURATIONS

PTFE mesh | PTFE coated fabric

Choose your enquiry specification below. Stock, final dimensions and operating suitability are confirmed in the quotation. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

BECCENTRIC (PVT) LTD
sales@beccentric.net | Mary: +263 780 864 277 | Tino: +263 779 098 357
Building 02, Luo Industrial, 1366 Ambleside Road, Aspindale, Harare

Specify your requirement

PTFE / Teflon Conveyor Belts

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Supply format	Endless finished belt, Open length, Replacement belt to sample
Finished belt length / circumference (mm)	Complete endless circumference, or open cut length
Finished belt width (mm)	Width across the belt
Fabric plies	1 ply, 2 ply, 3 ply
Joint / splice	Finger splice, Step / overlap splice, Mechanical fastener, Open ends - no joint, Match existing joint
Belt construction	PTFE-coated glass fibre
Total thickness (mm)	Measured total thickness, including covers
Surface / underside / colour	Smooth, rough top, coated, fabric back, colour
Flights, guides and edge details	Height, pitch, section, position and sidewalls
Smallest pulley / nosebar diameter (mm)	Include reverse bending and knife-edge details
Application and operating conditions	Product, duty, temperature and environment
Manufacturer / complete reference	Include every prefix, suffix and marking
Mesh opening (mm)	Opening in each direction, or solid fabric
Edge reinforcement	Reinforced, sealed or guided edges

INCLUDE WITH YOUR ENQUIRY

Length, width, mesh opening or fabric weave, thickness, joint, edge treatment, operating temperature, smallest pulley and original belt identification.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.