
PVC, PU & FABRIC BELTING

Rubber Conveyor Belts



Rubber conveyor belting for industrial handling, specified by carcass construction, cover grade, total thickness and finished width. Supply the belt marking and working conditions so tensile rating, splice and pulley suitability can be checked.

Unit for enquiry: metre | Product range

Product range reference. Colour and supplied configuration are confirmed with your quotation.

PRODUCT DETAILS

Range	Rubber Conveyor Belts
Dimensions	Width, length, thickness and joint to specification
Operating limits	Confirm the exact material and belt reference

TYPES / CONFIGURATIONS

Fabric reinforced rubber | Specify cover thickness

Choose your enquiry specification below. Stock, final dimensions and operating suitability are confirmed in the quotation. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

BECCENTRIC (PVT) LTD
sales@beccentric.net | Mary: +263 780 864 277 | Tino: +263 779 098 357
Building 02, Luo Industrial, 1366 Ambleside Road, Aspindale, Harare

Specify your requirement

Rubber Conveyor Belts

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Supply format	Endless finished belt, Open length, Replacement belt to sample
Finished belt length / circumference (mm)	Complete endless circumference, or open cut length
Finished belt width (mm)	Width across the belt
Fabric plies	1 ply, 2 ply, 3 ply
Joint / splice	Finger splice, Step / overlap splice, Mechanical fastener, Open ends - no joint, Match existing joint
Belt construction	Rubber cover
Total thickness (mm)	Measured total thickness, including covers
Surface / underside / colour	Smooth, rough top, coated, fabric back, colour
Flights, guides and edge details	Height, pitch, section, position and sidewalls
Smallest pulley / nosebar diameter (mm)	Include reverse bending and knife-edge details
Application and operating conditions	Product, duty, temperature and environment
Manufacturer / complete reference	Include every prefix, suffix and marking
Carcass rating / construction	EP or other rating; fabric construction and ply count
Top and bottom cover thickness (mm)	State each cover separately
Required cover grade	Abrasion, oil, heat or other specified duty

INCLUDE WITH YOUR ENQUIRY

Width, endless or cut length, carcass/tensile rating, plies, cover thicknesses, total thickness, conveyed product, load, pulley diameters and splice requirement.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.