STAINLESS STEEL & FITTINGS

Stainless Steel Threaded Sockets



Female-thread couplings for joining compatible threaded pipe ends. Select thread size and standard, then confirm the required grade and pressure-temperature duty.

Unit for enquiry: each | Product range

Product range example; confirm the make and configuration quoted.

PRODUCT DETAILS

Connection	Female threaded
Standard	Specify BSP or NPT; do not interchange
Material request	Specify stainless steel grade

TYPES / CONFIGURATIONS

Full socket / coupling | Half socket | Match existing socket

This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

BECCENTRIC (PVT) LTD
sales@beccentric.net | Mary: +263 780 864 277 | Tino: +263 779 098 357
Building 02, Luo Industrial, 1366 Ambleside Road, Aspindale, Harare

Specify your requirement

Stainless Steel Threaded Sockets

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Thread size	1/4 inch, 3/8 inch, 1/2 inch, 3/4 inch, 1 inch, 11/4 inch, 11/2 inch, 2 inch, 21/2 inch, 3 inch, 4 inch
Thread standard	BSP, NPT
Stainless steel grade	304, 316 / 316L
Length / dimensions (mm)	Overall length or required dimensions

INCLUDE WITH YOUR ENQUIRY

Thread size, BSP/NPT standard, grade, overall length, medium, pressure and temperature.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.