MOTORS, GEARBOXES & DRIVE COMPONENTS

# Stainless Steel Washdown Motors



Stainless motor options for wet-processing and cleaning-intensive food, beverage and dairy environments, selected for the actual washdown conditions.

Unit for enquiry: each | Product range

Product-family photograph. Exact model, dimensions and configuration are confirmed with your quotation.

## PRODUCT DETAILS

| | |
|---|---|
| **Construction** | Stainless housing / hardware on selected designs |
| **Surface** | Smooth, cleanable surfaces on hygienic designs |
| **Electrical & fit** | Voltage, frequency and IEC / NEMA dimensions to be matched |
| **Protection** | IP rating, seals, cable entries and cleaning compatibility confirmed per model |

## TYPES / CONFIGURATIONS

Foot-mounted stainless motor | Flange-mounted stainless motor | Replacement washdown motor | Application selection assistance

Stainless construction alone is not a food-contact approval or high-pressure washdown rating. Match the exact motor rating, cleaning regime and mounting standard. Choices record your requested specification; not every combination is available. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

# Specify your requirement

## Stainless Steel Washdown Motors

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

| | |
|---|---|
| **Requested motor power** | 0.18 kW, 0.37 kW, 0.55 kW, 0.75 kW, 1.1 kW, 1.5 kW, 2.2 kW, 3 kW, 4 kW, 5.5 kW, 7.5 kW, 11 kW, 15 kW, 18.5 kW, 22 kW, 30 kW, 37 kW, 45 kW, 55 kW, 75 kW |
| **Electrical supply and nameplate connection** | Phase, volts, Hz, delta / star connection and rated current |
| **Rated speed / pole count** | Nameplate rpm and poles; frequency if not 50 Hz |
| **Motor mounting requirement** | B3 foot, B5 flange, B14 small flange, B35 foot and flange, B34 foot and small flange, Vertical mounting - specify, Match existing mounting |
| **Frame, shaft and flange dimensions (mm)** | Frame / standard, shaft diameter x length, keyway, foot centres and flange drawing |
| **Application and environment** | Driven equipment, hours / starts, ambient temperature, dust and cleaning conditions |
| **Existing model / complete reference** | Full reference and suffixes; include a clear nameplate photograph |
| **Cleaning pressure, temperature and chemicals** | Method, water temperature / pressure, chemical concentration and exposure time |
| **Required protection and documentation** | IP rating, seal / material requirements and required declarations |

## INCLUDE WITH YOUR ENQUIRY

Send the complete reference and nameplate photo, installation dimensions, operating duty, quantity, delivery location and required date. State whether an alternative may be proposed for approval.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

## CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.