INDUSTRIAL & PROCESS VALVES

Triple-Offset Butterfly Valves



Triple-offset butterfly valves use eccentric geometry and a selected sealing design for demanding process duties. Match the body and disc materials, seat, face-to-face dimension, pressure-temperature envelope and operating torque. Specify the required leakage test standard; do not assume every butterfly valve has the same shut-off performance.

Unit for enquiry: each | Product range

Product-family reference photograph. The exact model, size, material and configuration are confirmed with your quotation.

PRODUCT DETAILS

Design	Triple-offset quarter-turn valve
Seating	Metal-seated arrangements to exact design
Connections	Specify end arrangement, standard and face-to-face
Duty	Isolation or approved control duty to selected model

TYPES / CONFIGURATIONS

Gear-operated triple-offset valve | Bare-stem valve for matching actuation | Pneumatic / electric assembly | Help me identify

Options describe your enquiry, not stock or a universal operating rating. Materials, connections, performance and supporting documents are confirmed for the exact item quoted. This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Triple-Offset Butterfly Valves

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Nominal size / measured connection dimensions	DN / NPS / tube OD, and any measured dimensions
Connection / end standard	BSP threaded, NPT threaded, Flanged - specify standard and class, Weld end - specify dimensions, Hygienic clamp - specify standard
Body, trim and sealing materials	Exact grade, seat, seals or existing specification
Operation required	Manual lever, Manual gearbox, Pneumatic spring return, Pneumatic double acting, Electric on/off, Modulating - specify signal
Medium, pressure and temperature	Fluid and concentration; min / normal / maximum pressure and temperature
Shut-off / performance requirement	Required leakage standard, flow direction and cycling
Existing reference / documents required	Model, nameplate, drawings, certificates and required date

INCLUDE WITH YOUR ENQUIRY

Send measured connections, the complete existing reference or photographs, operating conditions, quantity and required date. Include any drawings or certification required.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

View this product and choose specifications at beccentric.net

WhatsApp Mary: +263 780 864 277
WhatsApp Tino: +263 779 098 357
Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Prepared by Beccentric (Pvt) Ltd. Compiled 13 November 2026. Contact Beccentric to confirm the exact configuration and supporting documentation.